

■≢ PRO

Simple & Flexible Solution

LED FLEXIBLE LINEAR LIGHT

PRODUCT INFORMATION

- Excellently waterproof and anti-dust LED strips with professional design to guarantee lighting performance.
- It not only ensure high quality of lighting color consistency but also protect products outdoor against from harsh environments outdoors.

BENEFITS

- Water proof and vivid light color.
- Less maintenance cost and less concerns on water invasion.

FEATURES

- High CRI>92.
- Operating voltage DC226V.



AREAS OF APPLICATION





Hospitality

Shopping Center





Commercial

Educational Center


I TECHNICAL OPERATING & ELECTRICAL DATA

IP rating	IP65, PVC anti-UV
Power	7W/M (for all, each color will be divided accordingly)
PCB	Single PCB whole thickness 0.15mm, white color, 10mm, copper thickness 25ur
Chip size	5.0x5.0x1.2mm
L70	>20000H
Copper wire	0.15mm x 18pcs
Maximum length	40M / Reel
Culting unit	1 meter
Size	18x8mm
Other features	Each roll without controller (sold separately)

SPECIFICATIONS

Code No. Model No.		LED Quantity	Input	CCT	
611850	ILS08HVSTRGB01	60pcs/meter	DC226V	RGB	

DIMENSIONS





611850

ACCESSORIES LED FLEXIBLE LINEAR LIGHT CONNECTOR AVAILABLE AS AN ACCESSORY

Code No.	Model No.	IP	Power	Input	Output	Frequency	Dimensions
612417	ILSHVST2HFC02						
611791	ILSACSTPCCH02						1000x20.1x8mm
611937	ILSHVST2HFC02						L=200mm
611797	ILSHVST2H4PC01						L=300mm
611941	ILSHVRFRGBCD01	65	361W	DC226V	DC226V	433.92MHz	35x132x33mm
611929	ILS250HVFLLCG02	65	248W	AC220-240V	DC226V	50/60Hz	42x146x33mm
611930	ILS400HVFLLCG02	65	361W	AC220-240V	DC226V	50/60Hz	42x146x33mm

ACCESSORIES DIMENSIONS






612417 - Middle Connector

611791 - PVC Profile





611937 - Jumper

611941 - RGB Controller





APPLICATION PICTURE



LED FLEXIBLE LINEAR LIGHT

BEYOND LIGHT..
TO THE LAST DETAILS!

