

■≢ PRO

Simple & Flexible Solution

LED FLEXIBLE LINEAR LIGHT

| PRODUCT INFORMATION

- Excellently waterproof and anti-dust LED strips with professional design to guarantee lighting performance.
- It not only ensure high quality of lighting color consistency but also protect products outdoor against from harsh environments outdoors.
- ILLUS LED FLEXIBLE LINEAR Light gives the customer the flexibility to choose between 3 CCT tunable based on their specific need with lumen package 210 lm.

BENEFITS

- Water proof and vivid light color.
- Less maintenance cost and less concerns on water invasion.

FEATURES

- High CRI>92.
- Operating voltage DC226V.



AREAS OF APPLICATION





Hospitality

Shopping Center





Commercial

Educational Center


I TECHNICAL OPERATING & ELECTRICAL DATA

IP Rating	IP65, PVC
Power	8W/M
Lumen	210lm/M+/-10%
LED Quantity	72pcs/meter
PCB	Single PCB whole thickness 0.15mm, white color, 8mm, copper thickness 25ur
Chip Size	2.8x3.5x0.8mm
L70	>20000H
Input	DC226V
Copper Wire	0.18mm x 28pcs
Maximum Length	40 meters
Cutting Unit	1 meter cuttable
Size	26mmx16mm
Other Features	w/o CCT controller, sold separately

SPECIFICATIONS

Code No.	Model No.	Lumen	CRI	CCT
611840	ILS08HVNF92250TN01	210lm	92	2200K/5000K

DIMENSIONS




611840


ACCESSORIES LED FLEXIBLE LINEAR LIGHT CONNECTOR AVAILABLE AS AN ACCESSORY

Code No.	Model No.	IP	Power	Input	Output	Frequency	Dimensions
611951	ILSHVNFALMFCH02						1000x18.79x20mm
611936	ILSHVNF2H3PC02						L=200mm
611977	ILSHVNF2H3PC01						L=300mm
611940	ILSHVRFCCTCD01	65	361W	DC226V	DC226V	50/60Hz	35x88.5x33mm
611929	ILS250HVFLLCG02	65	248W	AC220-240V	DC226V	50/60Hz	42x146x33mm
611930	ILS400HVFLLCG02	65	361W	AC220-240V	DC226V	50/60Hz	42x146x33mm

I ACCESSORIES DIMENSIONS



611951 - Aluminum Profile



611936 - Jumper

611940 - CCT controller







LED FLEXIBLE LINEAR LIGHT

BEYOND LIGHT..
TO THE LAST DETAILS!

